

PAVIMENTI

floor tiles

GRES PORCELLANATO RETTIFICATO

rectified porcelain stoneware

UNI EN 14411 BIA GL



RET

Matt

V3



R10

20,2x122,2

R11

20,2x122,2 GRIP

9,5 mm



FORMATO

format



20,2x122,2

20,2x122,2 GRIP Grigio | Miele

Norway



NORWAY MIELE 20,2x122,2



NORWAY SBIANCATO 20,2x122,2

IMBALLI packing	mm	PZ box	MQ box	KG box	BOX pallet	MQ pallet	KG pallet	CODICE PREZZO price code
20,2x122,2 rett	9,5	4	0,99	19,73	48	47,52	960	CEX mq
20,2x122,2 GRIP rett	9,5	4	0,99	19,73	48	47,52	960	CEX mq

SBIANCATO



GRIGIO




MIELE




NOCE



PEZZI SPECIALI
special pieces



battiscopa 6,5x122,2
YBB |pz



CONSIGLI DI POSA
laying advice

SI CONSIGLIA UNA POSA SFALSATA MASSIMA A 1/4 ONDE EVITARE
PROBLEMI DI PLANARITÀ.

A staggered laying (max. 1/4) is highly recommended
in order to avoid flatness problems.